TECHNICAL DATA SHEET



HANSA CARE 7920 Macroemulsion of a modified siloxane as an ingredient for Home and Car Care.

Property

Product

Description

Aminosiloxanes are Siloxanes modifed with Nitrogen groups. The modification degree lead to an

optimal performance in aqueous or solvent borne formulations for home and car care applications.

These products are excellently suited for a use in polishes, way formulations and drying aids in automatic or manual car wash and provide for perfect drying characteristics including a good water repellence and excellent gloss.

Key Features

- Water repellency
- Durability
- Enhances Gloss and Color depth .
- Smoothness and Softness
- **Key Applications**
- Car Care
- Leather and Furniture Care
- Kitchen and Sanitary Cleaner

Fabric Care

Application

HANSA CARE 7920 can be used for car polishes, car sealants and impregnations for mineral and wood surfaces. The produc can be also used as an additive in fabric conditioners to enhan softness and product stability.

Health & Safety

Health & Safety

Safety Data Sheet available on request.

Packaging

Drums and bulk containers. Please contact our sales department for more information.

Revision Date	29 Apr 2021
Revision No	1
Download Date	18 May 2024

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com

	Appearance		Emulsion, slightly turbid liquid
IX	Chemistry		Macroemulsion of a reactive aminosiloxane
	Ionicity		Cationic
	MIT Free		Yes
	Non-Volatile Content (%)		Approx. 40
	Ultralow cyclic content		Yes
	Viscosity	Brookfield	< 100 cP
	pH (10% solution)		5.0 – 7.0
	Addition Rates		
	Dosage - 1		1.0 - 10.0% in car polishes
	Dosage - 2		0.5 - 4.0% in fabric care
	Dosage - 3		5.0 - 15.0% in impregnations
S	Storage		
t nce	Max Storage Temperature		40 °C / 104 °F
	Min Storage Temperature		4 °C / 39 °F

Test

Method

Value

12 mths

Emulsion, slightly turbid

Shelf Life