## TECHNICAL DATA SHEET



Method Value

White Liquid

Non-ionic

**55** % 7.5

0.1 - 1%

40 °C / 104 °F

40 lb. pails, 441 lb. drums,

2205 lb. totes, and tanker

## EM 1469 55% Active Emulsion of a 60,000 cSt Polydimethylsiloxane

**Property** 

**Product** 

Ionicity

Appearance

Solids Content (%)

**Addition Rates** 

Max Storage Temperature

Dosage - 1

Storage

Packaging

Shelf Life

Description

This product is an industrial nonionic polydimethylsiloxane emulsion.

**Key Features** 

Excellent wetting and spreading

High moleculare weight for extended performance

Easily dispersed in water with minimal agitation

**Key Applications** 

Release agent

Rubber treatment

Casting

Extrusion

**Application** 

EM 1469 is a 55% active emulsion of a high molecular weight silicone polymer. The high molecular weight dimethicone actives are delivered in an opaque, low viscosity liquid with neutral pH.

This emulsion was developed as an effective release agent at

low concentrations. EM 1469 is used in a variety of release applications as well as a leather conditioner, vinyl dressing and rubber treatment

**Use and Cure Information** 

To optimize the dispersion of this emulsion into the final formulation, it is recommended to add it slowly at the end of the procedure at a temperature below 40 °C (104 °F) with continuous mixing or stirring.

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

**Revision Date** 12 Feb 2024

Revision No

**Download Date** 09 May 2024

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.