TECHNICAL DATA SHEET



32 lb. pails or 325 lb.

EM 1642 High-end nonionic emulsion of silicone crosspolymer

Description	Property	Test	Value
This product is a emulsion of a crosspolymer gel.	-13	Method	
Key Features	Product		
Excellent surface leather conditionerImproves touch and surface slip	Appearance		Milk White
	Ionicity		Non-ionic
 Provides a light scattering matte effect 	MIT Free		Yes
Key ApplicationsLeatherAutomotive surfacesSynthetic surfaces	Solids Content (%)		8 %
	Ultralow cyclic content		No
	Viscosity (cst)		100000

Addition Rates

Dosage - 1 0.5 - 25

Storage

Max Storage Temperature 40 °C / 104 °F Min Storage Temperature 4 °C / 39 °F

Packaging drums

Shelf Life 12 mths

Tires **Application**

ICM EM 1642 is a emulsion of a crosspolymer gel that is designed for use on leather and other interior automotive surfaces to reduce glare and improve touch properties. ICM EM 1642 can also be used as a high end, long lasting slip aid for sliding windows and doors as well as an anti-squeak additive for automotive interiors.

Use and Cure Information

This product is compatiable with aqueous systems and can be added directly to the formulation with minor agitation.

Health & Safety

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Limitations

This product is not intended for pharmaceutical use.

Revision Date 21 Sep 2021

Revision No

Download Date 03 May 2024