TECHNICAL DATA SHEET



HANSA CARE 8014 D Modified siloxane as an ingredient for Home and Car Care.

Description

| Description | Property | Test Method | Value |
|---|--------------------------|----------------|-----------------------------------|
| Aminosiloxanes are Siloxanes modifed with Nitrogen groups. The modification degree lead to an | Product | | |
| optimal performance in aqueous or solvent borne formulations for | Appearance | | Colorless to yellow liquid |
| home and car care applications. | Chemistry | | Aminosiloxane |
| These products are excellently suited for a use in polishes, wax formulations and drying aids in automatic or manual car wash | Ionicity | | Cationic |
| and provide for perfect drying characteristics including a good | MIT Free | | Yes |
| water repellence and excellent gloss. | Nitrogen Content (%) | | Approx. 1.5 |
| Key Features | Non-Volatile Content (%) | | Approx. 100 |
| Water repellency | Ultralow cyclic content | | Yes |
| Beading effect | Viscosity | Brookfield | <100 cP |
| Fast drying effect in drying aids Improves Shine and Color depth | | 2.00.000 | |
| Key Applications | Addition Rates | | |
| Rinse Aids | Dosage - 1 | | 1.0 - 10.0% Rinse aids / Waxes |
| Car Polishes Sealants | Dosage - 2 | | 0.1 - 1.0% Glass treatment |
| Glass Treatments | Dosage - 3 | | 0.5 - 2.5% in Polishes |
| Application | - | | |
| HANSA CARE 8014 D is a high modified Aminosiloxane and | Storage | | |
| designed for the use as an ingredient in car wash products for the | Max Storage Temperature | | 40 °C / 104 °F |
| perfect drying result. HANSA CARE 8014 D works even in very | Min Storage Temperature | | 4 °C / 39 °F |
| low concentration and leaves a hydrophobic effect with an | Shelf Life | | 24 mths |
| extreme gloss after treatment. | | | |
| Health & Safety | | | |
| Health & Safety | | | |
| Safety Data Sheet available on request. | | | |
| Packaging | | | |
| Drums and bulk containers. Please contact our sales department for | or more information | | |

Drums and bulk containers. Please contact our sales department for more information.

| Revision Date | 29 Apr 2021 |
|---------------|-------------|
| Revision No | 1 |
| Download Date | 08 May 2024 |

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet. CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht.silicones.com

guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.