## **TECHNICAL DATA SHEET**



Condensation cure

1.19 g/cm3

insoluble

## HANSA MBC 37180 Mixture of OH-PDMS and reinforcing filler for producing condensation crosslinking silicones

Description Property Test Method Value

CHTs masterbatches are a mixture of silica and polysiloxane. Addition of the masterbatch is a convenient method of incorporating silica into an elastomer formulation to increase physical properties. The values for tensile, tear, and elongation typically increase commensurately with additional silica. Masterbatchs are typically suited specifically for condensation or addition cure chemistries. The compositions are solvent-free and typically low in cyclic siloxane content.

Product
Color Transparent
Non-Volatile Content (%) > 99
Shelf Life 12 mths
Ultralow cyclic content Yes
Viscosity Brookfield HTBD, 600000 cP

DIN 53479

**Key Features** 

containing silica

· containing OH-Siliconepolymer

translucent

good mechanical properties

**Key Applications** 

Intermediate for condensation curing formulations

**Use and Cure Information** 

Masterbatches are typically high viscosity and non-flowing. One

and viscosity profile to result in a flowable composition. Curing can be obtained with the addition of an appropriate crosslinker and catalyst system.

**Uncured Product** 

**Cured Product** 

Solubility - Water

Cure Type

Density

Solubility

must incorporate siloxane polymers of the appropriate chemistry

## **Health & Safety**

Please observe our safety data sheets and the safety remarks on our container labels when handling our products. The dangerous goods regulations and the accident prevention regulations of the professional associations must be particularly observed. Keep the EC safety data sheet of the applied product at hand since it provides you with useful instructions for the safe use and disposal of the product as well as for actions to be taken in case of accidents.

Revision Date 21 Feb 2023

Revision No

Download Date 08 May 2024