TECHNICAL DATA SHEET



ICM 1000 Methyltrimethoxy Silane

Description This additive is a silane that can readily react with a wide range of surfaces including organic polymers, glass, and ceramics.

Key Features

Effective coupling agent

Increases tensile, compression and modulus strenght to composites

Improves adhesion

Effective at low concentrations and has great compatibility with organic polymers and inorganic fillers.

Key Applications

Clay reinforced elastomers

Adhesion promoter

Nitrile rubber

Abrasive composites

Application

ICM 1000 is composed of methyltrimethoxy silane. ICM 1000

is used in formulation in order to improve adhesion and strength to a variety of substrates.

Test **Property** Value Method Product Appearance Clear liquid Color Clear BS ISO 1.037 g/cm3 Density 2781 Specific Gravity A 1.037 Viscosity (cst) 5

Storage

Shelf Life

Max Storage Temperature 40 °C / 104 °F

40 lbs Pails or 441 lbs Packaging Drums

24 mths

Structure of methyltrimethoxy silane

Use and Cure Information

This product is generally added to compositions at less than 1% in most formulations. Our product can be applied to surfaces as a dilute aqueous solution. It can also be mixed with water using light agitation.

Read product and safety data sheets before handling this product for physical and health hazard information. The safety data sheet is available from your CHT representative.

Revision Date 31 Aug 2021

Revision No 11

Download Date 08 May 2024

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.