TECHNICAL DATA SHEET



QGel 300Y High Strength, Yellow Tinted Silicone Gel

T . . .

Description

Description	Property	Test Method	Value
QGels are addition-cure clear, soft, moderately cross-linked silicone polymer. Silicone gels provide protection from moisture,	Uncured Product	Method	
vibration, thermal, or mechanical shock. Key Features	Cure Profile		30 mins at 150°C, 60 mins at 100°C, 20 hrs at 25°C
Soft, but has considerably higher strength than general	Cure Type		Addition
purpose silicone gels1:1 mix ratio	Density A	BS ISO 2781	0.97
 24-hour room temperature cure Dispensing equipment not necessary Use and Cure Information 	Density B	BS ISO 2781	0.97
Important	Gel Time at 25°C/77°F Mix Ratio By Weight		135 min 1:1
In order to achieve optimum performance, the same lot number of the A and B components should be used. Mixed lots may not	Rheology		Gel
obtain the performance criteria listed on the TDS or Certificate of Analysis.	Viscosity A Viscosity B	Brookfield Brookfield	•
The "A" part of QGels contain the platinum catalyst; great care should be taken when using automated dispensing equipment to	Cured Product		
not cross-contaminate systems.	Color		Yellow
Mixing	Max Working Temp		204 °C / 399 °F
Both the "A" and "B" parts should be well stirred to ensure the	Min Working Temp		-55 °C / -67 °F
material is uniform. QGels should be mixed by weight. Once the components are mixed, the curing process begins. The gel time of the mixed material is listed under the typical properties. Fast	Penetration (19.5g Cone Weight) mm		5 - 9 mm
curing gels should be dispensed utilizing automated mix and	Storage		
dispensing equipment. In order to achieve optimum performance, the same "A" and "B" side lot numbers should be used.	Max Storage Temperature		38 °C / 100 °F
	Shelf Life		24 mths

De-Aeration

Air trapped during mixing should be removed to eliminate voids in the cured product. Vacuum de-airing may be necessary to completely remove all entrapped air bubbles. To ensure proper de-airing, subject the mixed material to 29 inches of mercury.

Storage and Shelf-life

This product is best when used within 24 months from the date of manufacture, See product label and/or the CoA for specific "use by date". Product should be stored in its original, unopened container in an environment that does not exceed 38C (100F)

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case, the properties required for the intended use should be checked for quality assurance reasons.

Revision Date10 Nov 2021Revision No5Download Date05 May 2024

CHT Germany GmbH: Postfach 12 80, 72002 Tübingen, Bismarckstraße 102, 72072 Tübingen, Germany

Telephone: 07071/154-0, Fax: 07071/154-290, Email: info@cht.com, Homepage: www.cht.com / www.cht-silicones.com

The content set out in the technical data sheet does not contain information upon which you should rely. It is provided for general information purposes only and does not constitute a product specification. You must obtain professional or specialist advice before taking any action based on the information provided in the technical data sheet.

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.