## **TECHNICAL DATA SHEET**



# QGel 307IR Inhibition Resistant Silicone Gel

Description	Property	rest Method	value
QGels are addition-cure clear, soft, moderately cross-linked	<b>Uncured Product</b>		
silicone polymer. Silicone gels provide protection from moisture,	Color A		Transparent
vibration, thermal, or mechanical shock. <b>Key Features</b> • Inhibition Resistant	Color B		Transparent
	Gel Time at 25°C/77°F		22 mins
<ul><li>One to one mix ratio</li><li>Less than 30 minute room temperature cure</li></ul>	Specific Gravity A		0.97
Designed for automatic mixing and dispensing	Specific Gravity B		0.97
Use and Cure Information	Viscosity A	Brookfield	600 cP
Important	Viscosity B	Brookfield	425 cP

In order to achieve optimum performance, the same lot number of the A and B components should be used. Mixed lots may not

obtain the performance criteria listed on the TDS or Certificate of

The "A" part of QGels contain the platinum catalyst; great care should be taken when using automated dispensing equipment to not cross-contaminate systems.

**150C for 30 mins**Gel Hardness Brookfield **125 grams** 

Took Mathad Value

## Mixing

Daaauluslau

Both the "A" and "B" parts should be well stirred to ensure the material is uniform. QGels should be mixed by weight. Once the components are mixed, the curing process begins. The gel time of the mixed material is listed under the typical properties. Fast curing gels should be dispensed utilizing automated mix and dispensing equipment. In order to achieve optimum performance, the same "A" and "B" side lot numbers should be used.

#### **De-Aeration**

Air trapped during mixing should be removed to eliminate voids in the cured product. Vacuum de-airing may be necessary to completely remove all entrapped air bubbles. To ensure proper de-airing, subject the mixed material to 29 inches of mercury.

### Storage and Shelf-life

This product is best when used within 24 months from the date of manufacture, See product label and/or the CoA for specific "use by date". Product should be stored in its original, unopened container in an environment that does not exceed 38C (100F)

Storage beyond the date specified on the label does not necessarily mean that the product is no longer usable. In this case, the properties required for the intended use should be checked for quality assurance reasons.

Revision Date 20 Oct 2021

Revision No 3

Download Date 05 May 2024

CHT make reasonable efforts to ensure that information set out in the technical data sheet is complete, accurate, and up-to-date. CHT do not, however, make any representations, warranties or guarantees (whether express or implied) that information set out in the technical data sheet is complete, accurate, or up-to-date or that the product will be suitable for your requirements. You should carry out your own testing to determine the applicability of such information and whether the product will be suitable. CHT reserve the right to modify the technical data sheet at any time. The CHT technical service department is available to offer further information and advice and should it be needed to look at modifying current products or custom formulate a new one to meet your specific requirements. Please contact the technical service department.